

Specifications — CIA114F5

Video

Gain.....	Unity
Bandwidth.....	250 MHz (-3 dB)

Video input and loop through

Number/signal type.....	1 VGA–UXGA, Mac, Sun RGBHV, RGBS, RGsB 1 buffered local monitor loop-through identical to the input
-------------------------	--

NOTE *Sync is not stripped from green. RGsB input signals are output as RGBs.*

Connectors	2 female 15-pin HD
Nominal level	0.7 Vp-p for RGB
Minimum/maximum levels.....	Analog: 0.3 V to 1.5 Vp-p with no offset at unity gain
Impedance.....	75 ohms
Horizontal frequency.....	30 kHz to 130 kHz
Vertical frequency.....	30 Hz to 120 Hz
Return loss.....	<-50 dB @ 5 MHz

Video output

Number/signal type.....	1 RGBHV, RGBS, RGsB
Connectors	5 BNC female on 4" (10.2 cm) pigtails
Nominal level	0.7 Vp-p for RGB
Minimum/maximum levels.....	Analog: 0.3 V to 1.5 Vp-p
Impedance.....	75 ohms
Return loss.....	<-50 dB @ 5 MHz

Sync

Input type.....	RGBHV, RGBS, RGsB
Output type.....	RGBHV, RGBS, RGsB
Input level	2.0 V to 5.0 Vp-p
Output level	TTL: 5.0 Vp-p, unterminated
Input impedance	510 ohms
Output impedance	75 ohms
Max. propagation delay	1.2 μ s
Polarity.....	Positive or negative (follows input)

Audio

Gain.....	Unbalanced output: 0 dB; balanced output: +6 dB
Frequency response	20 Hz to 20 kHz, \pm 0.4 dB
THD + Noise.....	0.03% @ 1 kHz at nominal level, 0.1% @ 20 kHz at maximum output
S/N.....	>75 dB at maximum output
Stereo channel separation	>-113 dB @ 1 kHz to 20 kHz

Audio input

Number/signal type.....	1 stereo, unbalanced
Connectors	(1) 3.5 mm mini stereo jack
Impedance.....	>10k ohms unbalanced
Nominal level	-10 dBV (316 mV)
Maximum level.....	+8.1 dBu, (balanced or unbalanced) at 1%THD+N

NOTE *0 dBu = 0.775 Vrms, 0 dBV = 1 Vrms, 0 dBV \approx 2 dBu*

Audio output

Number/signal type.....	1 stereo, balanced/unbalanced
Connectors	1 direct insertion captive screw connector, 5 pole

Specifications — CIA114F5, cont'd

Impedance.....	50 ohms unbalanced, 100 ohms balanced
Gain error.....	±0.09 dB channel to channel
Maximum level (Hi-Z).....	>+15 dBu, balanced or unbalanced at 1%THD+N
Maximum level (600 ohm).....	>+13 dBm, balanced or unbalanced at 1%THD+N

General

External power supply.....	100 VAC to 240 VAC, 50/60 Hz, external; to 9 VDC, 0.6 A, regulated
Power input requirements.....	9 VDC, 0.5 A
Temperature/humidity.....	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing

Mounting

Floor box mount.....	Steel City® 665 floor box mountable
Enclosure type.....	Metal
Enclosure dimensions	
CIA114F5 faceplate.....	2.1" H x 5.75" W x 1.0" D (5.3 cm H x 14.6 cm W x 2.5 cm D)
Device.....	2.8" H x 1.9" W x 1.5" D (7.1 cm H x 4.8 cm W x 3.8 cm D) (Depth excludes connectors.)
Product weight.....	0.7 lbs (0.3 kg)
Shipping weight.....	3 lbs (2 kg)
Vibration.....	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Safety.....	CE, ETL (UL1950)
EMI/EMC.....	CE
MTBF.....	30,000 hours
Warranty.....	3 years parts and labor

NOTE All nominal levels are at ±10%.

NOTE Specifications are subject to change without notice.

7.6-112108-D5